

< SHARP>			< FTS 4335>	
PIN	name	obs	name	obs
1	B1B	LNB B power	idem	
2	B1A	LNB A power	idem	
3	B4	3,3 v booster	GND	
4	B2	3,3 v cx24118	GND	
5	nc		3.3v VT	
6	nc		TS1 D0	
7	nc		TS1 D1	
8	SDA	i2c	TS1 D2	
9	SCL	i2c	TS1 D3	
10	nc		TS1 D4	
11	B3		TS1 D5	
12	LNB 22K TX	3.3v	TS1 D6	
13	VDD	1.25v	TS1 D7	
14	RS data		TS1 CLK out	
15	RS data		TS1 valid	
16	RS data		TS1 Sync	
17	RS data		TS1 error	
18	RS data		AS1	
19	RS data		22K RX1	
20	RS data		22K TX1	
21	RS data		SDA	
22	RS-CLK		SCL	
23	RS-VALID		3.3VD	
24	RS-START		AS0	
25	RS-FAIL		1.1VD	
26	RESET		TS2 D0	
27			TS2 D1	
28			TS2 D2	
29			TS2 D3	
30			TS2 D4	
31			TS2 D5	
32			TS2 D6	
33			TS2 D7	
34			TS2 CLK out	
35			TS2 valid	
36			TS2 Sync	
37			TS2 error	
38			RESET	
39			22K RX2	
40			22K TX2	